

36"-HIGH LOCKING BAR HANDLES

Make it easy to leverage your body weight to open or close the container doors, compared to standard 20"H locking bar handles.

SECURE LOCKBOX

Features a thick metal casing to protect the padlock from bolt cutters and other break-in tools.

CSC PLATE

The CSC Safety approval plate guarantees that the container meets international safety standards and transport certifications.

DOOR SEALS

Built with 2-stage EPDM rubber which is water and weather resistant from -100°C to +300°C.



WEATHERPROOF VENTS

Help reduce heat, humidity and prevent condensation from forming.

CORTEN STEEL

Known for its unique rust-inhibitive properties, it gives containers durability and resistance to the elements.

PAINT

All our new shipping containers are painted with low VOC, water-based paint and zinc-enriched primer to ensure maximum resistance to the elements.

FORKLIFT POCKETS

Facilitate easy loading and unloading.

MARINE GRADE FLOORING

Consists of 1.1" thick, 19-ply marine grade plywood that can support up to 62,040lbs of payload and is treated to withstand spills and other contaminants.

WEIGHT & DIMENSIONS

Exterior: 20'L x 8'W x 8'6"H
 Interior: 19'9"L x 7'8"W x 7'10"H
 Door Opening: 7'8"W x 7'5"H

Forklift pockets: 14"W x 4"H
 Fork spread: 82"W center to center

Weight: 5,160 LBS
 Payload: 62,040LBS

MODIFICATION OPTIONS



Paint Decals Rollup Doors Garage Doors
 Ventilation Man Doors Windows Insulation

CONTAINER ACCESSORIES



Lockbox Padlock Puck lockbox Stacking pin
 Pipe Storage Insta Vents Shelving Deck Mount