





Help reduce heat, humidity and prevent condensation from forming.

PAINT

All our new shipping containers are painted with low VOC, water-based paint and zinc-enriched primer to ensure maximum resistance to the elements.

CORTEN STEEL

Known for its unique rust-inhibitive properties, it gives containers durability and resistance to the elements.

MARINE GRADE FLOORING

Consists of 1.1" thick, 19-ply marine grade plywood that can support up to 11,240lbs of payload and is treated to withstand spills and other contaminants.

DOOR SEALS

Built with 2-stage EPDM rubber which is water and weather resistant from -100°C to +300°C.

SECURE LOCKBOX

Features a thick metal casing to protect the padlock from bolt cutters and other break in tools.

36"-HIGH LOCKING BAR HANDLES

Make it easy to leverage your body weight to open or close the container doors, compared to standard 20"H locking bar handles.

FORKLIFT POCKETS

Facilitate easy loading and unloading.

CSC PLATE

The CSC Safety approval plate guarantees that the container meets international safety standards and transport certifications.

WEIGHT & DIMENSIONS

Exterior: 8'2"L x 6'6"W x 6'6"H Interior: 7'8"L x 6'3"W x 5'11"H Door Opening: 6'2"W x 5'9"H

Forklift pockets: 12.5"W x 4"H Fork spread: 35.5"W center to center

Weight: 1,850 LBS Payload: 9,170 LBS

MODIFICATION OPTIONS



CONTAINER ACCESSORIES

